

## SHIELDED CABLES



Flexible / Stranded Bare Copper Conductor, PVC Insulated, Overall Aluminium Mylar Tape Shielded with ATC Drain Wire and Outer PVC Sheathed Industrial Instrumentation (Shielded) Cables, Voltage Grade 300/500V, as per BS EN 50288-7

SIZE	Size in Sq.mm / Rate Per 100 Meter (in INR)					MOQ (KM)
	0.50	0.75	1.00	1.50	2.50	
2 Core	6650	8065	9394	12015	17669	3
3 Core	8322	10433	12398	16001	24560	3
4 Core	10409	13210	15863	20939	31675	3
5 Core	11961	15512	18841	25239	39338	3
6 Core	13977	18217	22422	29415	-	3
7 Core	15506	20457	25048	33483	51541	3
8 Core	17576	23291	28357	38362	61181	2
9 Core	19432	-	-	-	-	2
10 Core	21547	28650	35294	48419	75874	2
12 Core	24962	33500	41849	56562	89954	2
14 Core	28423	38009	48165	65379	105427	1
16 Core	32236	44149	54434	74117	120326	1
18 Core	35794	48705	60761	82837	135778	1
20 Core	39584	53408	67397	94866	150627	1
22 Core	43587	58952	73759	-	-	1
25 Core	48890	66352	83958	-	-	1
27 Core	52385	71227	89366	-	-	1

Note : Please contact to HO for Technical Data Sheet.