

CDINSD



connectwell
THE RIGHT CONNECTION

CDINSD : Din Rail Mounting Socket & Switch

Connectwell DIN Rail mounted socket and switches offer a unique possibility of mounting an Industrial Socket and Switch on a standard DIN rail.

Sockets are available for various country standard plugs. These need to be wired and snapped inside the Din rail mounting frame as shown in the assembly diagram below. This assembly then easily snaps on to a standard DIN rail.

TECHNICAL DATA

| | |
|------------------------------------|---------------------|
| Socket and Switch Housing Material | Polycarbonate |
| DIN-Rail Frame Material | ABS |
| Wire Clamp and Contact Material | Brass |
| Rated Minimum Wire Size | 0.5 mm ² |
| Rated Maximum Wire Size | 2.5 mm ² |
| Rated Voltage | 250 V |
| Rated Current | 16 A |

DIMENSIONS

| | |
|--------|-------|
| Height | 60 mm |
| Length | 82 mm |
| Width | 53 mm |

ORDERING INFORMATION

| CAT. NO. | DESCRIPTION | STD. PACK |
|----------|-----------------------------------|-----------|
| CDINSD | Din Rail Mounting Socket & Switch | 5 |

ACCESSORIES

| IMAGES | CAT. NO. | DESCRIPTION | STD. PACK |
|--------|---------------|--|-----------|
| | CA701-1M | Din 35 Rail unslotted 1 meter | 50 |
| | CA701-2M | Din 35 Rail unslotted 2 meter | 50 |
| | CA701-2M-S | Din 35 Rail slotted 2 meter | 50 |
| | CA701-1M-S | Din 35 Rail slotted 1 meter | 50 |
| | CA701-15-1M | Din 35 Rail 15 deep unslotted 1 meter | 50 |
| | CA701-15-1M-S | Din 35 Rail 15 deep slotted 1 meter | 50 |
| | CA701-15-2M | Din 35 Rail 15 deep unslotted 2 meter | 50 |
| | CA701-15-2M-S | Din 35 Rail 15 deep slotted 2 meter | 50 |
| | CA102 | End Clamp in Polyamide suitable for Din32 / Din35 / Din35-15 Rails | 50 |
| | CA202 | End Clamp in Polyamide suitable for Din 35 / Din 35-15 Rails | 25 |

ASSEMBLY INSTRUCTIONS



APPROVALS

