


CPDL1.5(I.S)



connectwell
THE RIGHT CONNECTION

1.5 sq.mm Multiple Connection Internally Shorted Terminal Blocks with 4 connection points.

These blocks are used to connect multiple wires in single Terminal Block, thereby eliminating reliability problems encountered when connecting multiple wires in a single clamp.

TECHNICAL DATA

| | |
|------------------------|-----------------------|
| Rated Voltage | 500 V |
| Rated Current | 15 A |
| Housing Material | Polymide |
| Standard Colour | Grey |
| Product Function | Double Level |
| Wire Entry Orientation | Top |
| Mounting Possibility | DIN 35/DIN 35-15 Rail |
| Rated Surge Voltage | 8 KV |
| Pollution Degree | 3 |

CONNECTION DATA

| | |
|---|---------------------|
| Conductor Cross Section Stranded min. | 0.2 mm ² |
| Conductor Cross Section Stranded max. | 1.5 mm ² |
| Conductor Cross Section AWG/Kcmil min | 24 AWG |
| Conductor Cross Section AWG/Kcmil max | 14 AWG |
| Conductor Cross Section Stranded with Ferrule/Lug min | 0.2 mm ² |
| Conductor Cross Section Stranded with Ferrule/Lug max | 1.0 mm ² |
| 2 Conductors with same Cross Section Stranded min | 0.2 mm ² |
| 2 Conductor with same Cross Section Stranded max | 1 mm ² |
| Conductor Cross Section Solid min | 0.2 mm ² |
| Conductor Cross Section Solid max | 1.5 mm ² |
| Stripping Length | 8 mm |

DIMENSIONS

| | |
|----------------------------------|---------|
| Height with DIN 35 x 15 mm rail | 52.8 mm |
| Height with DIN 35 x 7.5 mm rail | 45.3 mm |
| Length | 67.2 mm |
| Width (Thickness) | 3.5 mm |

ORDERING INFORMATION

| CAT. NO. | DESCRIPTION | STD. PACK |
|----------------|--|-----------|
| CPDL1.5(I.S) | 1.5 sq.mm 2 level Internally shorted Terminal Block | 50 |
| CPDL1.5(I.S)BU | 1.5 sq.mm 2 level Internally Shorted Terminal Block in Blue Colour | 50 |

ACCESSORIES

| IMAGES | CAT. NO. | DESCRIPTION | STD. PACK |
|--------|---------------|--|-----------|
| | CA701-1M | Din 35 Rail unslotted 1 meter | 50 |
| | CA701-2M | Din 35 Rail unslotted 2 meter | 50 |
| | CA701-2M-S | Din 35 Rail slotted 2 meter | 50 |
| | CA701-1M-S | Din 35 Rail slotted 1 meter | 50 |
| | CA701-15-1M | Din 35 Rail 15 deep unslotted 1 meter | 50 |
| | CA701-15-1M-S | Din 35 Rail 15 deep slotted 1 meter | 50 |
| | CA701-15-2M | Din 35 Rail 15 deep unslotted 2 meter | 50 |
| | CA701-15-2M-S | Din 35 Rail 15 deep slotted 2 meter | 50 |
| | CA103 | EndClamp in Polyamide suitable for Din 35/Din 35-15 rails | 50 |
| | CA104 | EndClamp in Polyamide suitable for Din 35/Din 35-15 rails | 50 |
| | JX1.5/2 | Shorting Link for 1.5 sq mm series | 100 |
| | JX1.5/3 | Shorting Link for 1.5 sq mm series | 50 |
| | JX1.5/4 | Shorting Link for 1.5 sq mm series | 50 |
| | JX1.5/10 | Shorting Link for 1.5 sq mm series | 10 |
| | EPCPDL1.5 | End Plate in Grey Colour | 50 |
| | MS3.5 | Marking Tag Blank suitable for 3.5mm Terminal Blocks | 100 |
| | TM3.5 | Flexible Marker Carrier for 3.5 mm thick double level Terminal Block | 50 |
| | MC3.5 | MARKER CARD 3MM PITCH WITH 90 TAGS | 10 |


APPROVALS



NOTES

The Rated current is with the use of copper (Cu) conductor/Wire

CPDL1.5(I.S)



connectwell
THE RIGHT CONNECTION

RATINGS AS PER STANDARDS

| STANDARDS | UL 1059 | CSA C.22.2 No:158 | IEC/EN60947-7-1 |
|---------------------------------------|----------------|--------------------------|------------------------|
| Approvals | UL | CSA | CE |
| Conductor Cross Section Stranded min. | 24 AWG | 24 AWG | 0.2 mm ² |
| Conductor Cross Section Stranded max. | 14 AWG | 14 AWG | 1.5 mm ² |
| Rated Voltage | 300 V | 300 V | 500 V |
| Rated Current | 15 A | 15 A | 15 A |