


CPDLG1.5



**connectwell**  
THE RIGHT CONNECTION

1.5 sq.mm Double Level Earthing Terminal Blocks.

These blocks are ideal for use in applications requiring high density wiring.

**TECHNICAL DATA**

|                        |                            |
|------------------------|----------------------------|
| Rated Voltage          | 500 V                      |
| Rated Current          | 15 A                       |
| Housing Material       | Polymide                   |
| Standard Colour        | Grey                       |
| Product Function       | Double Level Plus Earthing |
| Wire Entry Orientation | Top                        |
| Mounting Possibility   | DIN 35/DIN 35-15 Rail      |
| Rated Surge Voltage    | 8 KV                       |
| Pollution Degree       | 3                          |

**CONNECTION DATA**

|                                       |                     |
|---------------------------------------|---------------------|
| Conductor Cross Section Stranded min. | 0.2 mm <sup>2</sup> |
| Conductor Cross Section Stranded max. | 1.5 mm <sup>2</sup> |
| Conductor Cross Section AWG/Kcmil min | 24 AWG              |
| Conductor Cross Section AWG/Kcmil max | 14 AWG              |
| Conductor Cross Section Solid min     | 0.2 mm <sup>2</sup> |
| Conductor Cross Section Solid max     | 1.5 mm <sup>2</sup> |
| Stripping Length                      | 8 mm                |

**DIMENSIONS**

|                                  |         |
|----------------------------------|---------|
| Height with DIN 35 x 15 mm rail  | 52.8 mm |
| Height with DIN 35 x 7.5 mm rail | 45.3 mm |
| Length                           | 67.2 mm |
| Width (Thickness)                | 3.5 mm  |

**ORDERING INFORMATION**

| CAT. NO. | DESCRIPTION  | STD. PACK |
|----------|--|-----------|
| CPDLG1.5 | 1.5 sq.mm Feed Through + Grounding / Earthing Terminal Block | 50        |

**APPROVALS**




**NOTES**

The Rated current is with the use of copper (Cu) conductor/Wire

**RATINGS AS PER STANDARDS**

| STANDARDS | UL 1059 | CSA C. 22. 2 No:158 | IEC/EN60947-7-1 |
|-----------|---------|---------------------|-----------------|
| Approvals | UL      | CSA                 | CE              |

CPDLG1.5



**connectwell**  
THE RIGHT CONNECTION

RATINGS AS PER STANDARDS

| RATINGS AS PER STANDARDS              |        |        |                     |
|---------------------------------------|--------|--------|---------------------|
| Conductor Cross Section Stranded min. | 24 AWG | 24 AWG | 0.2 mm <sup>2</sup> |
| Conductor Cross Section Stranded max. | 14 AWG | 14 AWG | 1.5 mm <sup>2</sup> |
| Rated Voltage                         | 300 V  | 300 V  | 500 V               |
| Rated Current                         | 15 A   | 15 A   | 15 A                |