

CENC35



connectwell
THE RIGHT CONNECTION

35 sq.mm Neutral / Earth Clamps

The CENC series clamps are a flexible solution for terminating neutral and grounding wires on bus bar.

TECHNICAL DATA

Tightening Torque	2.5 Nm
Housing Material	Polymide
Product Function	Neutral/Earthing Clamps
Wire Entry Orientation	Side Entry
Mounting Possibility	Panel/Surface
Operated by	Screwdriver
Rated Surge Voltage	8 KV
Pollution Degree	3

CONNECTION DATA

Conductor Cross Section Stranded min.	10 mm ²
Conductor Cross Section Stranded max.	35 mm ²
Conductor Cross Section AWG/Kcmil min	8 AWG
Conductor Cross Section AWG/Kcmil max	2 AWG
Conductor Cross Section Stranded with Ferrule/Lug min	10 mm ²
Conductor Cross Section Stranded with Ferrule/Lug max	35 mm ²
2 Conductors with same Cross Section Stranded min	10 mm ²
2 Conductor with same Cross Section Stranded max	25 mm ²
Stripping Length	16 mm

DIMENSIONS

Length	27.3 mm
Width (Thickness)	14.5 mm

ORDERING INFORMATION

CAT. NO.	DESCRIPTION	STD. PACK
CENC35	35 sq.mm Neutral/Earth clamps Terminal Block in Green colour	50
CENC35BU	35 sq.mm Neutral/Earth clamps Terminal Block in Blue colour	50
CENC35BK	35 sq.mm Neutral / Earth Clamps Terminal Block in Black colour.	50
CENC35G	35 sq.mm Neutral / Earth Clamps Terminal Block in Grey colour.	50

ACCESSORIES

IMAGES	CAT. NO.	DESCRIPTION	STD. PACK
	CA202	End Clamp in Polyamide suitable for Din 35 / Din 35-15 Rails	25

ACCESSORIES

IMAGES	CAT. NO.	DESCRIPTION	STD. PACK
	CA509/K6	Blank Marking Tag	100
	NES	Plastic support with fixing screw for fixing 10 / 6 mm Bus Bar suitable for mounting CENC4 / CENC16 / CENC35 Earth / Neutral Clamps	50
	SCS1/5.5	Electricians Screwdriver for slotted screws	10
	NEB6	6mm Bus Bar for mounting CENC4 / CENC16 / CENC35 Earth / Neutral Clamps	1
	NEB10	10mm Bus Bar for mounting CENC4 / CENC16 / CENC35 Earth / Neutral Clamps	10
	MC6	MARKER CARD 6MM PITCH WITH 72 TAGS	10

APPROVALS



NOTES

The Rated current is with the use of copper (Cu) conductor/Wire

CENC35



connectwell
THE RIGHT CONNECTION

RATINGS AS PER STANDARDS

STANDARDS	UL 1059	CSA C.22.2 No:158	DIN EN60947-7-1
Approvals	UL	CSA	VDE
Conductor Cross Section Stranded min.	8 AWG	8 AWG	10 mm ²
Conductor Cross Section Stranded max.	2 AWG	2 AWG	35 mm ²
Tightening Torque	25 lb-in	25 lb-in	2.5 Nm

STANDARDS	IEC/EN60947-7-1
Approvals	CE
Conductor Cross Section Stranded min.	10 mm ²
Conductor Cross Section Stranded max.	35 mm ²
Tightening Torque	2.5 Nm